



N.P.T. S.R.L. A SOCIO UNICO

Revision nr. 3

Dated 03/07/2023

Printed on 13/07/2023

Page n. 1/16

Replaced revision:2 (Printed on: 25/11/2022)

SILCOFLEX 583

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **SILCOFLEX 583**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Sealant for high temperature, contains Polysiloxanes and acetoxy curing agents.**

Consumer uses [C], professional uses [PW] - Product categories: Adhesives, sealants.
Uses advised against - Do not use for purposes other than those indicated.

1.3. Details of the supplier of the safety data sheet

Name **N.P.T. S.R.L. A SOCIO UNICO**
Full address **via Guido Rossa 2**
District and Country **40053 Valsamoggia - Loc. Crespellano (BO)**
Italia
Tel. +39 051 969109
Fax +39 051 969837

e-mail address of the competent person
responsible for the Safety Data Sheet **infoSDS@nptsrl.com**

1.4. Emergency telephone number

For urgent inquiries refer to **Please contact your near local poison control center**
Laboratories and manufactory plant - Villanova d'Ardenghi (PV)
+39 0382 400140 (avaiable from Monday to Friday, only in the following office hours:
8.30-12.30, 13.30-17.00) Laboratories and manufactory plant VALSAMOGGIA (BO)
+39 051969068 office hours (8.30-13; 14-17.30), from Monday to Thursday.

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).
However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

**SILCOFLEX 583**

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

Precautionary statements: --

Product not intended for uses provided for by Directive 2004/42/EC.

2.3. Other hazardsOn the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

During crosslinking it develops ACETIC ACID (CAS 64-19-7) by hydrolysis of Triacetoxysilanes.

Flam. Liq. 3 H226, Skin Corr. 1A H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B
Skin Corr. 1A H314: \geq 90%, Skin Corr. 1B H314: \geq 25%, Skin Irrit. 2 H315: \geq 10%, Eye Dam. 1 H318: \geq 25%, Eye Irrit. 2 H319: \geq 10%**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Ethyl/Methyl acetoxy silane (oligomers)		
INDEX	$1,5 \leq x < 2$	Skin Corr. 1B H314, Eye Dam. 1 H318
EC		
CAS -		
REACH Reg. n.a.		
Triacetoxylethylsilane		
INDEX -	$1,5 \leq x < 2$	Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, EUH014
EC 241-677-4		STA Oral: 500 mg/kg
CAS 17689-77-9		
REACH Reg. 01-2119881778-15		
triacetoxymethylsilane		
INDEX -	$1,5 \leq x < 2$	Acute Tox. 4 H302, Skin Corr. 1C H314, Eye Dam. 1 H318, EUH014
EC 224-221-9		STA Oral: 500 mg/kg
CAS 4253-34-3		
REACH Reg. 01-2119962266-32		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Ethyl/Methyl acetoxy silane (oligomers)
Impurezza (addotto generato in situ non isolabile).



SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

Water jets. Use water jets only to cool the surfaces of containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**SILCOFLEX 583****6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 10

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ «σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelmére
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à

**SILCOFLEX 583**

POL	Polska	exposição durante o trabalho a agentes cancerígenos ou mutagénicos Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

**ACETIC ACID
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV	CZE	25	10,025	50	20,05	
AGW	DEU	25	10	50 (C)	20 (C)	
MAK	DEU	25	10	50	20	
TLV	DNK	25	10			E
VLA	ESP	25	10	50	20	
VLEP	FRA	25	10	50	20	
HTP	FIN	13	5	25	10	
TLV	GRC	25	10	37	15	
AK	HUN	25		50		
GVI/KGVI	HRV	25	10	50	20	
VLEP	ITA	25	10	50	20	
TLV	NOR	25	10	50	20	
TGG	NLD	25		50		
VLE	PRT	25	10	50	20	
NDS/NDSch	POL	25		50		
TLV	ROU	25	10	50	20	
NGV/KGV	SWE	13	5	25	10	
NPEL	SVK	25	10	50	20	
MV	SVN	25	10	50	20	
WEL	GBR	25	10	50	20	
OEL	EU	25	10	50	20	
TLV-ACGIH		25	10	37	15	

Triacetoxyethylsilane

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,2	mg/l
Normal value in marine water	0,02	mg/l

**N.P.T. S.R.L. A SOCIO UNICO**

Revision nr. 3

Dated 03/07/2023

Printed on 13/07/2023

Page n. 6/16

Replaced revision:2 (Printed on: 25/11/2022)

SILCOFLEX 583

Normal value for fresh water sediment	0,16	mg/kg
Normal value for marine water sediment	0,016	mg/kg
Normal value for fresh water, intermittent release	1,7	mg/l
Normal value of STP microorganisms	1	mg/l
Normal value for the terrestrial compartment	0,031	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	65 mg/m3		10,8 mg/m3		32,5 mg/m3		32,5 mg/m3	

triacetoxymethylsilane
Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	0,1	mg/l
Normal value for fresh water sediment	0,8	mg/kg
Normal value for marine water sediment	0,08	mg/kg
Normal value for water, intermittent release	10	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,13	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1 mg/kg/d				
Inhalation	5,1 mg/m3		5,1 mg/m3					25 mg/m3
Skin		7,2 mg/kg/d	7,2	7,2 mg/kg/d				14,5 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of

**SILCOFLEX 583**

various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

ADDITIONAL INDICATIONS (PPE)

Hand Protection - Protective gloves in butyl rubber (Material thickness:> 0.3 mm, breakthrough time:> 480 min). Nitrile rubber gloves (Material thickness:> 0.1 mm; breakthrough time: 60-120 min).

Respiratory Protection - Gas Filter ABEK (certain gases and vapors inorganic and organic acids; ammonia / amines), in accordance with recognized standards such as EN 14387.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	paste	
Colour	black	
Odour	characteristic (vinegar)	
Melting point / freezing point	not applicable	
Initial boiling point	not applicable	
Flammability	not available	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	65 °C	Method:ISO 3679
Auto-ignition temperature	> 400 °C	
Decomposition temperature	> 300 °C	
pH	not available	Reason for missing data:Non miscible / Not miscible
Kinematic viscosity	20,5 mm ² /s	Temperature: 40 °C
Dynamic viscosity	ca. 1000000 mPa*s	Method:Brookfield
Solubility	immiscible with water	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	not available	
Density and/or relative density	1,02 - 1,04	
Relative vapour density	> 1 (Air=1)	
Particle characteristics	not applicable	

9.2. Other information

Ref. to 9.2 solubility in water: hydrolytic decomposition occurs. pH: the product has acid reaction with water.

Explosion limits for released acetic acid: 4-17% Vol.

**SILCOFLEX 583****9.2.1. Information with regard to physical hazard classes**

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	1,00 % - 10,30 g/litre
Explosive properties	not applicable
Oxidising properties	not applicable
Can pressure:	Not applicable

SECTION 10. Stability and reactivity**10.1. Reactivity**

Information not available

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

ACETIC ACID

Risk of explosion on contact with: chromium (VI) oxide, potassium permanganate, sodium peroxide, perchloric acid, phosphorus chloride, hydrogen peroxide. May react dangerously with: alcohols, bromine pentafluoride, chlorosulphuric acid, dichromate-sulphuric acid, ethane diamine, ethylene glycol, potassium hydroxide, strong bases, sodium hydroxide, strong oxidising agents, nitric acid, ammonium nitrate, potassium tert-butoxide, oleum. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Protect from moisture.

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

ACETIC ACID

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Reacts with: water, basic substances and alcohols. The reaction takes place with formation of acetic acid.

ACETIC ACID

Incompatible with: carbonates, hydroxides, phosphates, oxidising substances, bases.

10.6. Hazardous decomposition products

In the case of hydrolysis: acetic acid. Measurements have shown that at temperatures higher than 150 ° C, for oxidative decomposition, is liberated a small amount of formaldehyde.



SILCOFLEX 583

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

In the face of available data there are no acute toxic effects after a single dermal exposure. Given the available data there are no acute toxic effects after a single oral exposure.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

ACETIC ACID

LD50 (Dermal):	1060 mg/kg Rabbit
LD50 (Oral):	3310 mg/kg Rat
LC50 (Inhalation vapours):	11,4 mg/l/4h Rat



SILCOFLEX 583

Triacetoxymethylsilane

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

triacetoxymethylsilane

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Non-irritating (< 5% acetoxymethylsilanes) Bridging principle "Substantially similar mixtures" (Rabbit, OECD 404).

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Non-irritating (< 5% acetoxymethylsilanes) Bridging principle "Substantially similar mixtures" (Rabbit, OECD 405).

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE



SILCOFLEX 583

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Given the physico-chemical properties of the product, there is no danger of aspiration.

Does not meet the classification criteria for this hazard class Viscosity: 20,5 mm²/s

11.2. Information on other hazards

In the presence of humidity, the product releases a small amount of acetic acid which has an irritating effect on the skin and mucous membranes.

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Analysis on the basis of physical and chemical properties: no harmful effects on the organisms present in the water. At present experiences are no adverse effects on water purification plants.

12.2. Persistence and degradability

Silicone content: not biodegradable. The product of hydrolysis (acetic acid) is easily biodegradable.

ACETIC ACID

Solubility in water > 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

Unlikely bioaccumulation.

ACETIC ACID

Partition coefficient: n-octanol/water -0,17

12.4. Mobility in soil

Polymeric component: insoluble in water. In the cured state is insoluble in water. Good water separation by filtration.



SILCOFLEX 583

ACETIC ACID

Partition coefficient: soil/water 1,153

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

The valid EEC waste code are largely source-related; the manufacturer is, therefore, unable to specify waste codes for products used in various sectors.

Small quantities of hardened product can be treated come Urban Solid Waste or industrial waste similar to USW.

CER-code (suggested) : 08 04 10

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable



SILCOFLEX 583

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

**SILCOFLEX 583**Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

Indications of International Registration Status - Listed in or corresponding to the following inventories:

REACH - Europe

AREC - South Korea

AICS - Australia

DSL - Canada

IECSC - China

PICCS - Philippines

TSCA - USA

TCSI - Taiwan

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

The result of the safety assessment does not require the indication of exposure scenarios and uses in the safety data sheet.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
EUH014	Reacts violently with water.
EUH210	Safety data sheet available on request.

**SILCOFLEX 583****LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy



N.P.T. S.R.L. A SOCIO UNICO

Revision nr. 3

Dated 03/07/2023

Printed on 13/07/2023

Page n. 16/16

Replaced revision:2 (Printed on: 25/11/2022)

SILCOFLEX 583

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 09 / 11 / 12 / 15.